



Article no.: M-2687

**Product data:**  
**Behälter 2.200 Liter aus V2A einwandig,  
ungebraucht,  
Standing**

EUR 12.500,00

zzgl. 19 % MwSt. excl. shipping

in stock: 1

Location: 33378 Rheda-Wiedenbrück

Behälter 2.200 Liter aus V2A einwandig, ungebraucht consists of the material 1.4301(AISI304) V2A. The volume is approx. 2,200 litres.

Behälter 2.200 Liter aus V2A einwandig, ungebraucht was last used in the following area: .

1 pieces of Behälter 2.200 Liter aus V2A einwandig, ungebraucht is/are currently still available. Delivery can take place worldwide.

## Product description

## General

---

**Material in contact with product** 1.4301(AISI304) V2A

**Volume approx.** 2,200 litres

**Structure** Standing

**DIN design** unknown

**Year of manufacture** 2012

**Manufacturer** P+W Metallbau

**Condition** Used

## Dimensions approx.

---

**External diameter** 1500 mm

**Cyl. height** 1290 mm

**Outlet height** 250 mm

**Total height** 3500 mm

## Design

---

**Weight approx.** 1800 kg

**Insulation** No

**Interior surface** Smoothed

**Exterior surface** Smoothed

**Floor type** Torispherical bottom

**Head design** Flat bottom

## Equipment

---

**Temperature-controllable** No

**Operating temperature** 50 °C

## Agitator

---

**Agitator quantity** 1 (piece)

**Agitator position** Head off-centre

**Agitator type** Head off-centre

## **Supports**

---

**Supports** Stainless steel feet  
**Number of feet** 4 (piece)

## **Fixtures and fittings**

---

**Outlet nozzle** 200  
**Fixtures and fittings**  
**Additional fixtures and fittings** Nameplate,

## **Other notices**

---

**Technical documentation** Designation  
**Note** Schuettgewicht 1800 kg/cbm

# Pictures



P+W METALLBAU			
Fabrik-Nr. serial number	8003580	Behältergewicht item weight	kg
Behälter-Nr. item number	V-100	Baujahr year built	2012
Inhalt capacity	m <sup>3</sup>	Schüttgewicht bulk density	1800 kg/m <sup>3</sup>
Füllgut product	SLURRY		
max. zul. Ueberdruck max. adm. overpressure	+4.5 mbar	max. zul. Unterdruck max. adm. underpressure	=5 mbar
max. red. Explosionsdruck max. red. explosion press.	bar (pred)	statischer Ansprechdruck stat. response pressure	bar (pstat)
max. Betriebstemperatur max. operating temp.	50 °C	Werkstoff material	1.4301
<b>Metal-, Behälter- und Anlagenbau</b> <b>D-88074 Meckenbeuren</b> Tel. +49 (0) 7542 / 9420-0 Fax +49 (0) 7542 / 9420-10			

# Terms and conditions

The general terms and conditions of Georg Heuer Behälterhandel und Industriebedarf GmbH apply. [View here.](#)